

# HUS Series 2/2 Solenoid Valve(Normal Close)



## HUS

2/2 Solenoid Valve (N.C.)



High Temperature

### How to Order?

Series No.	Port Size	Voltage	Orifice	Body Material
HUS	10: 3/8" 15: 1/2" 20: 3/4" 25: 1" 35: 1-1/4" 40: 1-1/2" 50: 2" F: Flange connections	E1: AC110V E2: AC220V E4: DC24V	15L=15.0mm 20L=20.0mm 25L=25.0mm 35L=35.0mm 40L=40.0mm 50L=50.0mm	S2: SS304 Stainless steel body

#### Order Example:

HUS series solenoid valve, 2/2, AC110V, 3/8 port size, orifice 15mm, Stainless steel body, ERP code is HUS10E1-15LS2

### Specifications

Model	Port size	Orifice (mm)	CV	The pressure difference			Max. fluid temperature (°C)
				Min. pressure	Max. working pressure		
					Heat conduction oil	Steam	
HUS10E2-15LS2	3/8"	15	4.5	0.5	16	16	250
HUS15E2-15LS2	1/2"	15	4.5	0.5	16	16	250
HUS20E2-20LS2	3/4"	20	8	0.5	16	16	250
HUS25E2-25LS2	1"	25	12	0.5	16	16	250
HUS35E2-35LS2	1-1/4"	35	22	0.5	16	16	250
HUS40E2-35LS2	1-1/2"	35	22	0.5	16	16	250
HUS50E2-50LS2	2"	50	45	0.5	16	16	250
HUSFE2-25LS2	Flange	25	12	0.5	16	16	250
HUSFE2-32LS2	Flange	32	22	0.5	16	16	250
HUSFE2-40LS2	Flange	40	22	0.5	16	16	250
HUSFE2-50LS2	Flange	50	45	0.5	16	16	250